

2016 HINO 155



A Toyota Group Company

CAB OVER ENGINE GVW: 14,500 LBS. BBC: 66.5" ENGINE MODEL: J05E-TP

After 100 years in the business, Hino has got it right with the J05E Series engines for Light Duty trucks. At 210 HP producing 440 lb.-ft. torque, the Hino 155 cab-over truck delivers not just on performance, but long term durability and low cost operation as well. Quality, durability, and reliability are the foundation of Hino Trucks legendary owner loyalty. And we didn't sacrifice economy. A combination of the J05E Engine, optimized SCR, aerodynamics, and Aisin's 6 speed autotransmission means the new Hino COE models deliver on expectations for fuel economy too.



HINO.COM



2016 HINO 155

CAB OVER ENGINE GVW: 14,500 LBS. BBC: 66.5" ENGINE MODEL: J05E-TP



ENGINE

Model	HINO J05E-TP
Type	Diesel 4-cycle, 4-cylinder in-line, water-cooled, dry cylinder line
Fuel System	Common Rail, Direct injection type. (Denso)
Max. output (SAE Gross)	210hp at 2,500 rpm.
Max. torque (SAE Gross)	440 lb.-ft. at 1,500 rpm.
Engine displacement	5L

POWERTRAIN AND PERFORMANCE

GVW	14,500 lbs. GVW		
Powertrain	STD	OPT	OPT
Max. speed mph	77.7	73	69.6
Rear Axle Gear Ratios	4.625	4.875	5.142

Transmission	Model	Aisin A465 (PTO capable)	
	Type	Six speed automatic	
Ratios	1st	3.742	
	2nd	2.003	
	3rd	1.343	
	4th	1.000	
	5th	0.773	
	6th	0.634	
	Rev	3.539	
Tire size	215/75R17.5		

DIMENSIONS

Cab Type		Standard	Standard	Standard
Wheelbase	in.	137.8	149.6	173.2
Useable cab to axle	in.	110	121.9	145.5
Cab to body clearance	in.	5.8	5.8	5.8
Rear overhang	in.	46.3	46.3	46.3

FRAME HEIGHT AT

Front axle	in.	28.2	28.1	27.9
Rear axle	in.	31.9	32.0	31.9

WEIGHT CAPACITIES

Front axle	lbs.	5,360 - 5,950
Rear axle	lbs.	13,670
Front spring	lbs.	5,950
Rear spring	lbs.	9,877

AXLE / SUSPENSION

Front axle	Reversed Elliot, "I" beam.
Front spring	Taper-leaf springs shock absorbers and stabilizer.
Rear axle	Full-floating, single reduction; Single-speed by hypoid gearings.
Rear spring	Taper-leaf springs shock absorbers.

FRAME

Ladder type	Straight section	
Width	in.	33
Yield strength	PSI	56,900
Resisting bending moment (one side) (114.2, 137.8, 149.6, 161.4WB)	in.-lbs.	706,900 (no reinforcement)

WHEELS / TIRES

6 Wheels	16X6K-127 6-stud disc
Wheel style	Steel, painted
6 Tires	215/75R17.5
Tire pattern	Fr-Rib Rr-All Season

BRAKES

Service brake	Hydraulic system with disc brake for front and rear wheels.
Parking brake	Mechanical, internal expanding acting on transmission output shaft.
Exhaust brake	Electric-pneumatic with valve in exhaust pipe.

CHASSIS EQUIPMENT

Fuel tank	STD. - Center mount 30 gal. OPT. - Side mount 33 gal.
Fuel pre-filter	Heated fuel water separator.
Radiator grille	Chrome
DEF tank	4.7 gal.

ELECTRICAL EQUIPMENT

Batteries	Two, parallel connection, each 12V
Alternator	12V, 130A, brushless
Starter	12V, 4.5hp, Denso
Auxiliary Switches	11 vacant switch blanks for body and equipment use.
Stereo	AM/FM radio with CD Player

POPULAR OPTIONAL EQUIPMENT

Cab paint, exterior - Black, red, yellow, blue, green
INSIGHT 2.0 Telematics System
Transmission PTO capable
Bluetooth radio
Seat, driver's - Magnetic suspension with arm rest

HINOWATCH (service free of charge)

- 3 year unlimited roadside assistance
- Lockout Service
- Battery Jumpstart
- Warranty Towing (2 year coverage)

HINOCARE (service free of charge)

Hino trucks includes a 2-year or 60,000 mile preventive service care program for the 155/155-DC diesel model called HinoCare. All 2013MY through 2016MY 195 and 195-DC models are also eligible.

NOTES

All specifications of the products are with normal manufacturing allowances and tolerances. Hino Motors Sales U.S.A., Inc. reserves the right to alter specifications at any time without previous notice.



A Toyota Group Company