

# 2016 HINO 195



A Toyota Group Company

CAB OVER ENGINE GVW: 19,500 LBS. BBC: 66.5" ENGINE MODEL: J05E-TP

After 100 years in the business, Hino has got it right with the J05E Series engines for Light Duty trucks. At 210 HP producing 440 lb.-ft. torque, the Hino 155 cab-over truck delivers not just on performance, but long term durability and low cost operation as well. Quality, durability, and reliability are the foundation of Hino Trucks legendary owner loyalty. And we didn't sacrifice economy. A combination of the J05E Engine, optimized SCR, aerodynamics, and Aisin's 6 speed auto transmission means the Hino COE models deliver on expectations for fuel economy too.



[HINO.COM](http://HINO.COM)





# 2016 HINO 195

CAB OVER ENGINE GVW: 19,500 LBS. BBC: 66.5" ENGINE MODEL: J05E-TP



## ENGINE

Model	HINO J05E-TP
Type	Diesel 4-cycle, 4-cylinder in-line, water-cooled, dry cylinder line
Fuel System	Common Rail, Direct injection type. (Denso)
Max. output (SAE Gross)	210hp at 2,500 rpm.
Max. torque (SAE Gross)	440 lb.-ft. at 1,500 rpm.
Engine displacement	5L

## POWERTRAIN AND PERFORMANCE

GVW	19,500 lbs.	
GCWR	25,500 lbs.	
Powertrain	STD	OPT
Max. speed mph	68.4	64.6
Startability (% of grade)	27.2	28.6
Rear Axle Gear Ratios	5.571	5.857

Transmission	Model	Aisin A465 (PTO capable)
	Type	Six speed automatic
Ratios	1st	3.742
	2nd	2.003
	3rd	1.343
	4th	1.000
	5th	0.773
	6th	0.634
	Rev	3.539
Tires (standard)	225/70R19.5	

## DIMENSIONS

Cab Type		Standard	Standard	Standard	Standard	Standard
Wheelbase	in.	114.2	137.8	149.6	161.4	173.2
Useable cab to axle	in.	86.4	110	121.9	133.7	145.5
Cab to body clearance	in.	5.8	5.8	5.8	5.8	5.8
Rear overhang	in.	46.3	46.3	46.3	46.3	46.3

## FRAME HEIGHT AT

Front axle	in.	29.7	29.6	29.6	29.5	29.5
Rear axle	in.	33.4	33.4	33.5	33.5	33.5

## WEIGHT CAPACITIES

Front axle	lbs.	6,830 - 7,270
Rear axle	lbs.	13,660
Front spring	lbs.	6,830
Rear spring	lbs.	13,660

## AXLE / SUSPENSION

Front axle	Reversed Elliot, "I" beam.
Front spring	Taper-leaf springs shock absorbers and stabilizer.
Rear axle	Full-floating, single reduction; Single-speed by hypoid gearings.
Rear spring	Taper-leaf springs shock absorbers.

## FRAME

Ladder type	Straight section	
Width	in.	33
Yield strength	PSI	56,900
Resisting bending moment (one side)	in.-lbs.	353,450 - 423,050 (no reinforcement)

## WHEELS / TIRES

6 Wheels	19.5X6 6-stud disc.
Wheel style	Steel, painted
6 Tires	225/70R19.5
Tire pattern	Fr-Rib Rr-All Season

## BRAKES

Service brake	Hydraulic system with disc brake for front and rear wheels.
Parking brake	Mechanical, internal expanding acting on transmission output shaft.
Exhaust brake	Electric-pneumatic with valve in exhaust pipe.

## CHASSIS EQUIPMENT

Fuel tank	STD. - Center mount 30 gal. OPT. - Side mount 33 gal.
Fuel pre-filter	Heated fuel water separator.
Radiator grille	Chrome
DEF tank	4.7 gal.

## ELECTRICAL EQUIPMENT

Batteries	Two, parallel connection, each 12V
Alternator	12V, 130A, brushless
Starter	12V, 4.5hp, Denso
Auxiliary Switches	9 vacant switch blanks for body and equipment use.
Stereo	AM/FM radio with CD Player

## POPULAR OPTIONAL EQUIPMENT

Cab paint, exterior - Black, red, yellow, blue, green, silver
GVW Derate 17,950 (factory order only)
INSIGHT 2.0 Telematics System
Transmission PTO
Bluetooth radio

## HINOWATCH (service free of charge)

- 3 year unlimited roadside assistance
- Lockout Service
- Battery Jumpstart
- Warranty Towing (2 year coverage)

## HINOCARE (service free of charge)

Hino trucks includes a 2-year or 60,000 mile preventive service care program for the 155/155-DC diesel model called HinoCare. All 2013MY through 2016MY 195 and 195-DC models are also eligible.

## NOTES

All specifications of the products are with normal manufacturing allowances and tolerances. Hino Motors Sales U.S.A., Inc. reserves the right to alter specifications at any time without previous notice.



A Toyota Group Company